## interstuhl

## Technical data sheet 400B

Specification Four legs

Dimensions in mm			
	Seat:	H:	470
		W:	450
		D:	410
	Total:	H:	930
		W (no ArmR):	485
		D:	540
		D.	540
Packaging data	Weight:	kg	7
	Volume:	m³	0,4



Basic equipment		Benefit
Backrest	Upholstered mesh backrest (10 mm Schaum). Carrier material, backrest (from the back) always black.	
Upholstery	Seat upholstery: 55 mm foam.	Great seating comfort.
Frame	Tubular steel frame Ø 22 x 2,5 mm, powder coated as colour finish (plastic parts).	
Seat carrier.	Plastic.	
Stackability.	6 chairs.	
Plastic parts	Colour maintained throughout, black.	Colourfast and resistant to deep scratches and abrasions.
Glides	Plastic glides for soft floors.	Ideal stability.
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Standards	EN 16139 for visitor chairs. GS-Symbol for tested safety and tested for contaminants.	High-quality and great comfort.
Certification	Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability. Blue Angel, Bifma e3 level Platin.	High-quality product.
Warranty and return	10 years warranty. Complete return and recycling guarantee.	Exchange of parts free of charge within the guaranteed periods.

Disassembly instructions are available upon request for any interstuhl product

## Technical data sheet 400B

Specification Four legs

			ollections in various colours.	Ideal stability and protection of the floor.	
		Felt glides for ha			
Frame Powder coated		brilliant silver or chromed.	Optical design.		
Plastic parts and frame		White.		Optical design.	
Options				Benefit	
	, oralled				
Packaging data	Weight: Volume:	kg m³	7 0,4	and press	
		D:	540		
		W (no ArmR):	485		
	Total:	H:	930		
		D:	410		
		W:	450		
	Seat:	H:	470		

Disassembly instructions are available upon request for any interstuhl product

