# interstuhl

### Technical data sheet EV261

Specification Swivel chair medium high, mesh, FLEXTECH

| Dimensions in mm | Backrest: | H:           | 640     |
|------------------|-----------|--------------|---------|
|                  | Seat:     | H:           | 415-540 |
|                  |           | W:           | 520     |
|                  |           | D:           | 450     |
|                  | Total:    | H:           | 1135    |
|                  |           | W (no ArmR): | 520     |
|                  |           | W (ArmR):    | 685     |
|                  |           | D:           | 595     |
| Packaging data   | Weight:   | kg           | 15,7    |
|                  | Volume:   | m³           | 0,2     |
|                  |           |              |         |



| Basic equipment        |   | Benefit  |
|------------------------|---|--|
| Plastic parts          | Colour maintained throughout, black or white.   | Always look good even with intensive use.  |
| Backrest               | Backrest medium high, mesh covered, black.  |  |
| Upholstery             | Seat upholstery: 53 mm foam.  | Upholstery is unglued, ensuring optimal air movement, breathable.  |
| Mechanism              | Synchronous mechanism, lockable, with<br>FLEXTECH Inside. Large opening angle of up to<br>max. 106° with additional side tilt of 5°. Backrest<br>lockable in 4 positions. | Synchronous mechanisms of Interstuhl are designed in a way that they help to support optimally the body in every seating position and at the same time they relieve the change between the different seating positions. This is also aided by FLEXTECH and enables dynamic 3D sitting. |
| Seat height adjustment | Seat height adjustment infinitely variable from 415 - 540 mm. Self-supporting safety gas spring.  | People measuring with a height between 151 and 192<br>cm (Acc. to DIN EN 1335) can individually adjust the<br>seat height in the most ergonomic way.   |
| Weight Adjustment      | From 45 - 120 kg, multilevel.   | Individual adjustment of the backrest and the back pressure to the weight and height of the user.  |
| Seat inclination       | Integrated seat tilt feature thanks to FLEXTECH<br>Inside, 5° to the side, 5° to the front.   | The inclination means that the pelvis is at a steeper<br>angle and the spine is straightened, thus preventing<br>rounding of the back. FLEXTECH expands the range of<br>movement in all directions and therefore guarantees<br>healthier, dynamic sitting.                             |
| Castors Ø 65 mm        | Hard double castors, black, load dependent braked, for soft floors. (Acc. to DIN EN 12529).   | The chair does not roll away in an off-loaded position.  |
| Base                   | Polyamide base, colour maintained throughout, black or white.   | Always look good even with intensive use.  |
| Materials              | All materials are pure and recyclable.  | Environmentally friendly.  |
| Standards              | EN 1335 for office swivel chairs and office swivel<br>armchairs. GS-Symbol for tested safety, tested<br>for contaminants, Ergonomics approved. BIFMA.                     | High level of safety and great comfort.  |

#### **Technical data sheet EV261**

Certification

Warranty

Specification Swivel chair medium high, mesh, FLEXTECH

| Dimensions in mm | Backrest: | H:           | 640     |
|------------------|-----------|--------------|---------|
|                  | Seat:     | H:           | 415-540 |
|                  |           | W:           | 520     |
|                  |           | D:           | 450     |
|                  | Total:    | H:           | 1135    |
|                  |           | W (no ArmR): | 520     |
|                  |           | W (ArmR):    | 685     |
|                  |           | D:           | 595     |
| Packaging data   | Weight:   | kg           | 15,7    |
|                  | Volume:   | m³           | 0,2     |
|                  |           |              |         |

Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System

DIN EN ISO 14001:2015, Occupational Health and Safety Management System DIN EN ISO 45001:2018, Energy management system DIN

Commitment to sustainability, Quality Office, Blue Angel, Bifma e3 level Platin.

EN ISO 50001:2018, EcoVadis Gold,

warranty conditions.

10 year warranty according to our current



High-quality product.

Quality guaranteed to last for entire product life.

## interstuhl

# interstuhl

#### Technical data sheet EV261

Specification Swivel chair medium high, mesh, FLEXTECH

| Dimensions in mm | Backrest: | H:           | 640     |
|------------------|-----------|--------------|---------|
|                  | Seat:     | H:           | 415-540 |
|                  |           | W:           | 520     |
|                  |           | D:           | 450     |
|                  | Total:    | H:           | 1135    |
|                  |           | W (no ArmR): | 520     |
|                  |           | W (ArmR):    | 685     |
|                  |           | D:           | 595     |
| Packaging data   | Weight:   | kg           | 15,7    |
|                  | Volume:   | m³           | 0,2     |
|                  |           |              |         |



Benefit

#### Options

| Seat height adjustment | Seat height adjustment infinitely variable:<br>Self-supporting safety gas spring low: 400 - 445<br>mm; Self-supporting safety gas spring high: 475<br>- 610 mm.  | Even for people taller than 192 cm and smaller than 151 cm is offered the correct ergonomic seating posture.  |
|------------------------|--|---|
| Castors/Glides         | Soft double castors, black, load dependent braked, for hard floors or glides. (Acc. to DIN EN 12529).  | The chair does not roll away in an off-loaded position.   |
| Base                   | Brilliant silver or polished aluminium base.   | Very high stability, long service life. High-quality look.  |
| Seat depth adjustment  | Sliding seat for an individual adjustment of the seat depth, area of adjustment: 60 mm.  | The seat depth can be individually adjusted to ensure an optimal support surface of the thighs. Too little (lack of support) or too much (congestion of the bloodstream in the region of the popliteal fossa) can be avoided. |
| Lumbar support         | Height adjustable (50 mm) or height (70 mm) and depth adjustable (up to 15 mm).  | The lumbar support is height adjustable or height and depth adjustable and can be adapted to the corporal conditions of the user.   |
| Armrests               | 2D T-armrests, height and width adjustable, soft<br>surface. 3D T-armrests, height, width and depth<br>adjustable, soft surface. 4D T-armrests, height,<br>width and depth adjustable, rotatable, soft<br>surface. | The armrests relieve the neck and shoulder muscles.   |
| Material (fabric)      | Various fabric and leather options are available as well as different mesh colours.  | Individual design.  |
| Accessories            | Coat hanger, black or white.   |   |