

Technical data sheet HU173

Specification HUB 1 pod low, one-seater conf pod, with dec stitch

Dimensions in mm

| | | | |
|----------------|---------|----------------|------|
| | Total: | H: | 1350 |
| | | W (no ArmR): | 2480 |
| | | D: | 1125 |
| Packaging data | Weight: | kg | |
| | Volume: | m ³ | |



Basic equipment

Benefit

| | | |
|----------------------|--|---|
| General | Meeting module, covered with laminated fabric on both sides, with decorative seams all round. Central opening on one side. | Acoustically and visually shielded. |
| Frame | Aluminium profile frame, 2480 x 1350 x 55 mm (W x H x D), in black or white. | Attractive look. |
| Cover materials | Various fabric qualities in various colours. | Individual design. |
| Glides | Glides with levelling of up to 10 mm. | Firm contact with the floor and height adjustment. |
| Materials used | All materials are unmixed and recyclable. | Environmentally friendly. |
| Standards | GS-symbol for tested safety. Tested for absence of harmful substances. | High level of safety. |
| Certification | Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Occupational Health and Safety Management System ISO 45001:2018, EcoVadis Gold. | High-quality product. |
| Warranty and returns | 10 year warranty according to our current warranty conditions. | Quality guaranteed to last for entire product life. |

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet HU173

Specification HUB 1 pod low, one-seater conf pod,with dec stitch

Dimensions in mm

| | | | |
|----------------|---------|----------------|------|
| | Total: | H: | 1350 |
| | | W (no ArmR): | 2480 |
| | | D: | 1125 |
| Packaging data | Weight: | kg | |
| | Volume: | m ³ | |



Options

Benefit

| | | |
|----------------------|---|--|
| Acoustic performance | Sound-absorbing polyester panels integrated across entire surface, 50 mm thick. | For perfect sound absorption and insulation. |
| Screen mount | Universal screen mount, recommended for screens up to 40". Cable duct integrated in the pod wall runs from the screen mount to underneath the table. | Ideal for presentations. |
| Table | Decorative melamine faced board (MFC), (20 mm) with ABS edge in same colour as tabletop (black, premium white or oak). Table leg made from high-pressure die cast aluminium, in black or white, with inlay in same colour. L/W/H:600x600x723 mm. | |
| Table power supply | Integrated socket with sliding cover incl. type F outlet, HDMI and USB charging port, white. | Direct connection to screen. |
| Covered inlay | With fabric, same as wall cover. | Visual highlight. |

Disassembly instructions are available upon request for any interstuhl product