

Technical data sheet HU275

Specification HUB 2 pod high,two-seater conf pod,high w dec stit

Dimensions in mm

Packaging data	Total:	H:	1900
		W (no ArmR):	2480
	D:	1625	
	Weight:	kg	
	Volume:	m³	



Basic equipment

Benefit

General	Meeting module, covered with laminated fabric on both sides, with decorative seams all round. Central opening on one side.	Acoustically and visually shielded.
Frame	Aluminium profile frame, 2480 x 1900 x 55 mm (W x H x D), in black or white.	Attractive look.
Cover materials	Various fabric qualities in various colours.	Individual design.
Glides	Glides with levelling of up to 10 mm.	Firm contact with the floor and height adjustment.
Materials used	All materials are unmixed and recyclable.	Environmentally friendly.
Standards	GS-symbol for tested safety. Tested for absence of harmful substances.	High level of safety.
Certification	Quality management system DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Occupational Health and Safety Management System ISO 45001:2018, EcoVadis Gold.	High-quality product.
Warranty and returns	10 year warranty according to our current warranty conditions.	Quality guaranteed to last for entire product life.

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet HU275

Specification HUB 2 pod high,two-seater conf pod,high w dec stit

Dimensions in mm

Packaging data	Total:	H:	1900
		W (no ArmR):	2480
	D:	1625	
	Weight:	kg	
	Volume:	m ³	



Options

Benefit

Acoustic performance	Sound-absorbing polyester panels integrated across entire surface, 50 mm thick.	For perfect sound absorption and insulation.
Ambient light	Ambient light/transformer LED lighting fitted to inside of surrounding aluminium profile. Light intensity and warmth can be controlled with supplied remote control or via an app.	Indirect lighting without the need for additional lamps.
Screen mount	Universal screen mount, recommended for screens up to 40". Cable duct integrated in the pod wall runs from the screen mount to underneath the table.	
Table	Decorative melamine faced board (MFC), (20 mm) with ABS edge in same colour as tabletop (black, premium white or oak). Table leg made from high-pressure die cast aluminium, in black or white, with inlay in same colour. L/W/H:875x600x723 mm.	
Table power supply	Integrated socket with sliding cover incl. type F outlet, HDMI and USB charging port, white.	Direct connection to screen.
Covered inlay	With fabric, same as wall cover.	Visual highlight.

Disassembly instructions are available upon request for any interstuhl product