

Technical data sheet SU114

Specification Visitor chair, Four legs, fully upholstered

Dimensions in mm	Backrest:	H:	400
		Seat:	H: 440
	Total:	W:	460
		D:	450
		H:	830
		W (no ArmR):	540
Packaging data	Weight:	kg	8,6
		Volume:	m³ 0,3
		W (ArmR):	580
		D:	515



Basic equipment

Benefit

Seat and Backrest	Seat and back: polypropylene shell with Flex-Function. Ergonomically shaped; fully upholstered.	High quality appearance and ergonomic sitting.
Upholstery	Foam thickness: 10 mm, pad thickness approx. 15 mm.	Good seating comfort.
Frame	Four legged: Steel tube, powder-coated, white or black. Round tube Ø: 18 mm. Wall thickness: 2 mm.	Very good stability, longevity. The coating ensures an attractive surface even with intensive use.
Stackability	Stacking height: 5 pieces. Stacking protection included. If loop armrests are selected, the model will no longer be stackable.	Space-saving stowage possibility.
Glides	Plastic glides for soft floors, black.	Optimum stability.
Materials	All materials are pure and recyclable.	Environmentally friendly.
Standards	GS-symbol for tested safety, tested for contaminants. BIFMA tested.	High level of safety and comfort.
Certification	Quality Management System DIN EN ISO 9001:2015, Regulation (EC) no. 1221/2009 (EMAS), Environmental Management System DIN EN ISO 14001:2015, Occupational Health and Safety Management System DIN EN ISO 45001:2018, Energy Management System DIN EN ISO 50001:2018, EcoVadis Gold. Commitment to sustainability. Blue Angel, Bifma e3 level Platin.	High-quality product.
Warranty	10 year warranty according to our current warranty conditions.	Quality guaranteed to last for entire product life.

Technical data sheet SU114

Specification Visitor chair, Four legs, fully upholstered

Dimensions in mm	Backrest:	H:	400	
		Seat:	H:	440
			W:	460
			D:	450
	Total:	H:	830	
		W (no ArmR):	540	
		W (ArmR):	580	
D:		515		
Packaging data	Weight:	kg	8,6	
	Volume:	m³	0,3	



Options

Benefit

Materials (fabric)	Various fabrics in a variety of colours are available.	Individual design.
Frame	Four legged: Steel tube, chromed. Round tube Ø: 18 mm. Wall thickness: 2 mm.	Very good stability, longevity. High quality appearance.
Glides	Felt glides for hard floors, black.	Optimum stability of the chair. Spares the floor.
Armrests	Open armrest or loop armrest (round tube Ø16 mm) in frame colour with black rubber pad.	The armrests relieve the neck and shoulder muscles.
Row connector	Extendable row connector, chrome-plated.	Ability to connect chairs to rows of chairs.