

Technical data sheet V101K

Specification Four legged with seat upholstered, plastic shell

Dimensions in mm	Backrest:	H:	420
	Seat:	H:	445
		W:	445
		D:	415
	Total:	H:	820
		W (ArmR):	510
		D:	565
Packaging data	Weight:	kg	6,3
	Volume:	m³	0,37



Basic equipment Benefit Seat and Backrest Seat and backrest made of plastic ergonomically-formed, backrest height 290 mm. Upholstery Seat upholstered. Great seating comfort. Frame Very high stability, longevity. High-quality look. Chrome-plated frame with eliptically-shaped steel tube 30 x 15 x 2 mm. Technically patented. Stackability Stacking heigh of the vertical stacking: 20 Space-saving storage. chairs. Plastic parts White. Highly durable 2-component shell. Very high stability, longevity. High-quality look. Polypropelene with fibreglass core. Glides Plastic glides for soft floors, black. Optimum stability of the chair. Protection of the floor. Materials All materials are segregated and recyclable. Environmentally friendly. Standards High safety and comfort. DIN EN 16139 four leg and chantilever. GS-symbol for tested safety, tested for contaminants. Certification High-quality product. Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability. Blue Angel. Warranty and return 10 years warranty. Complete return and Exchange of parts, free of charge, within the guaranteed recycling guarantee. period.

Disassembly instructions are available upon request for any interstuhl product



Technical data sheet V101K

Specification Four legged with seat upholstered, plastic shell

Dimensions in mm	Backrest:	H:	420
	Seat:	H:	445
		W:	445
		D:	415
	Total:	H:	820
		W (ArmR):	510
		D:	565
Packaging data	Weight: Volume:	kg m³	6,3 0,37



Options		Benefit	
Plastic parts	Anthracite, light grey.	Optical design variety	
Glides	Felt glides for hard floors, black.	Optimum stability of the chair. Protection of the floor.	
Armrests/Accessories	Armrests with plastic pad, row connector, panic bolt.	Optimal function extension depending on individual usage.	

Disassembly instructions are available upon request for any interstuhl product